

INSULATION HOSE Product Offerings

Blown insulation is an economical and time-saving way to install insulation in any construction project. Hi-Tech Duravent's selection of insulation hoses take you from the removal of the old insulation, the de-humidification of the space and the re-application of new insulation. Built for the demands of the insulation industry, these hoses are designed to be long-lasting and effective in getting the job done.



IBH

TEMPERATURE RANGE: -30°F to 130°F

CONSTRUCTION: Polyethylene wall with Polyethylene helix

STANDARD COLORS: Clear with frosted helix

STANDARD LENGTH: 50'

FEATURES/BENEFITS:

- Perfect choice for the blowing of insulation
- Great crush resistance
- Easy to drag, durable exterior
- Interior texture fluffs the insulation as it blows out
- Non-marking external helix
- Tough interior to handle the rigors of insulation blowing
- Clear wall to locate blockages

APPLICATIONS:

- Insulation Blowing
- Ventilation
- Exhaust
- Dehumidification

INDUSTRIES:

- Rental Equipment
- Insulation Blowing Equipment
- Dehumidifier Equipment
- Air/Fume Removal Equipment

ID (in)	WORKING PRESSURE (psi)	VACUUM RATING (inHg)	BEND RADIUS	COMPRESSION RATIO	OD (in)	WALL THICKNESS	APPROX. WEIGHT (lb/ft)
1.5	31	>29	2.5	1:0.75	2	0.021	0.16
2	29	>29	3	1:0.75	2.5	0.024	0.24
2.5	25	20	4.5	1:0.75	3	0.024	0.29
3	22	12	5	1:0.75	3.5	0.024	0.37
3.5	18	10	5.5	1:0.75	4	0.024	0.44
4	15	8	6	1:0.75	4.5	0.024	0.47

- ABRASION-RESISTANT
- DRAG-RESISTANT
- CHEMICAL-RESISTANT

- LIGHTWEIGHT
- FLEXIBLE
- MOISTURE-RESISTANT





WPE

TEMPERATURE RANGE: -30°F to 160°F

CONSTRUCTION: Polyethylene and UV additive reinforced with bronze coated stainless steel helix

STANDARD COLOR: Clear

STANDARD LENGTHS: 25', 50'

FEATURES/BENEFITS:

- Perfect choice for the removal of insulation
- Wire-reinforced for excellent crush resistant
- Easy to drag, durable exterior
- Moisture resistant and no exposed wire, great for dehumidification
- Non-marking exterior
- Tough interior to handle the rigors of insulation removal
- Clear wall to locate blockages

APPLICATIONS:

- Insulation Removal
- Ventilation
- Exhaust
- Dehumidification

INDUSTRIES:

- Rental Equipment
- Insulation Removal Equipment
- Dehumidifier Equipment
- Air/Fume Removal Equipment

ID (in)	WORKING PRESSURE (psi)	VACUUM RATING (inHg)	BEND RADIUS	COMPRESSION RATIO	OD (in)	WALL THICKNESS	APPROX. WEIGHT (lb/ft)
4	14	20	8	1:0.75	4.29	0.030	0.54
6	10	13	12	1:0.75	6.29	0.030	0.90
8	6	10	16	1:0.75	8.35	0.030	1.21
10	5	6	20	1:0.75	10.38	0.030	1.61
12	4	4	24	1:0.75	12.38	0.030	1.93

- ABRASION-RESISTANT
- DRAG-RESISTANT
- CHEMICAL-RESISTANT

- LIGHTWEIGHT
- MOISTURE-RESISTANT
- UV-RESISTANT