

Sta-Flex³⁶⁰

- HOSE FULLY EXPANDS TO 32" AND COMPRESSES TO 12" WITH A 2.5" DIAMETER
- VERY FLEXIBLE - STAYS IN POSITION WHEN BENT, FLEX FATIGUE AND ABRASION RESISTANT
- EASY TO COMPRESS AND STORE AWAY TO SAVE SPACE
- HOSE INCLUDES TWO 2.5" DIAMETER SWIVEL CUFFS THAT SWIVEL AT 360° AND FIT MOST STANDARD ACCESSORIES
- GREAT FOR DUST COLLECTION, FUME EXTRACTION, AND VACUUM APPLICATIONS



HI-TECH
DURAVENT
Flexible Hose & Ducting

www.hitechduravent.com

© 2011 Hi-Tech Duravent



RFH

TEMPERATURE RANGE: -60° F to 275° F (intermittent to 300° F)
CONSTRUCTION: Thermoplastic rubber reinforced with a wire helix
STANDARD COLOR: Black
STANDARD LENGTHS: 25', 50' (available up to 100')
SIZE RANGE: 1-1/4" to 24"



CVD

TEMPERATURE RANGE: -20° F to 180° F
CONSTRUCTION: Polyvinylchloride reinforced with a wire helix
STANDARD COLOR: Clear or blue
STANDARD LENGTH: 25', 50'
SIZE RANGE: 1" to 18"



UFD

TEMPERATURE RANGE: -65° F to 200° F
CONSTRUCTION: Thermoplastic polyurethane reinforced with a wire helix
STANDARD COLORS: Clear or black
STANDARD LENGTHS: 25', 50'
SIZE RANGE: 2" to 18"



Dust-Flex PU (Polyurethane)

TEMPERATURE RANGE: -40° F to 200° F
CONSTRUCTION: 2-ply thermoplastic polyurethane material with wire helix
STANDARD COLOR: Smoke grey
STANDARD LENGTH: 10', 20'
SIZE RANGE: 2-1/2" and 4"



Dust-Flex PVC (Polyvinylchloride)

TEMPERATURE RANGE: -20° F to 165° F (intermittent to 180° F)
CONSTRUCTION: All clear construction PVC reinforced with a wire helix
STANDARD COLOR: Clear with black wire helix
STANDARD LENGTH: 10', 20', 50'
SIZE RANGE: 2-1/2" and 4"

For more information visit www.hitechduravent.com or call us at 800.348.6500

1177 Markley Drive
Plymouth, IN 46563

528 Carwellyn Road
Abbeville, SC 29620

2755 Dos Aarons Way
Vista, CA 92081

4610 Eastgate Parkway,
Unit 3
Mississauga, Ontario
Canada L4W 3W6



HI-TECH
DURAVENT
Flexible Hose & Ducting
www.hitechduravent.com