

RFH Ultra

Physical Characteristics, Pressure & Flex Values

ID	Working Pressure	Vacuum	CL Bend Radius	Compress Ratio	OD Nominal	Wall Thickness	Weight
(in.)	(psi)	(inHg)	(in.)		(in.)	(in.)	(lbs./ft.)
1.00	25	14	1.00	1:5:1	1.25	.020	.12
1.5	22	14	2.00	2:4:1	1.69	.020	.16
2.00	20	14	3.00	2:3:1	2.25	.022	.20
3.00	10	14	4.00	2:3:1	3.25	.025	.34
4.00	8	14	5.00	2:1:1	4.25	.025	.58
5.00	6	10	7.00	2:1:1	5.50	.025	.64
6.00	4	6	8.00	2:1:1	6.50	.025	.70

Pressure and Vacuum data based on straight lengths of hose at ambient temperature 72° F.

Construction: Thermoplastic rubber reinforced with yarn and a coated wire helix
Temperature range: -60° F to 275° F (intermittent to 325° F)
Standard color: Black
Standard lengths: 25', 50'

www.hitechduravent.com

smiths

528 Carwellyn Road, Abbeville, SC 29620 • 1177 Markley Drive, Plymouth, IN 46563 • Tel: 800-348-6500
 4610 Eastgate Parkway, Unit 3, Mississauga, Ontario, Canada L4W 3W6 • Tel: 905-602-9660 • Fax: 800-348-6599