

TBH-W

Physical Characteristics, Pressure & Flex Values

ID	Working Pressure	Vacuum	CL Bend Radius	Compress Ratio	OD Nominal	Wall Thickness	Weight
(in.)	(psi)	(inHg)	(in.)		(in.)	(in.)	(lbs./ft.)
2.00	23	30	2.25	1:8	2.45	0.030	.26
2.50	20	30	3.50	1:8	2.85	0.030	.33
3.00	17	30	4.25	1:7	3.42	0.030	.43
4.00	15	28	4.75	1:7	4.42	0.030	1.29
5.00	11	20	5.75	1:7	5.42	0.030	1.21
6.00	10	16	6.75	1:7	6.42	0.030	1.24
7.00	8	14	8.00	1:7	7.46	0.030	1.44
8.00	7	12	9.00	1:7	8.46	0.030	1.74
10.00	5	6	10.50	1:6	10.47	0.030	2.08
12.00	3	4.5	11.75	1:6	12.47	0.030	2.27

Pressure and Vacuum data based on straight lengths of hose at ambient temperature 72° F.

Construction:	Polypropylene with a wire helix and a polypropylene wearstrip
Temperature range:	-10° F to 225° F
Standard color:	Black with a green wearstrip
Standard lengths:	25', 50'